

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
6 November 2003 (06.11.2003)

PCT

(10) International Publication Number
WO 03/091520 A1

- (51) International Patent Classification⁷: E05C 19/00
- (21) International Application Number: PCT/GB03/01626
- (22) International Filing Date: 16 April 2003 (16.04.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0209173.4 23 April 2002 (23.04.2002) GB
- (71) Applicant (for all designated States except US): **WIL-LEARN LIMITED** [GB/GB]; 131 Silverbirch Road, Kingshurst, Birmingham, West Midlands B37 6AT (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **GRIFFIN, Alexander, Ernest** [GB/GB]; 131 Silverbirch Road, Kingshurst, Birmingham, West Midlands B37 6AT (GB). **WHELAN, William, Brendan, John** [GB/GB]; 10 Rotherhams Hill, Baddesley Ensor, Atherstone, Warwickshire CV9 2DR (GB).
- (74) Agent: **JACKSON, Derek, Charles**; Derek Jackson Associates, The Old Yard, Lower Town, Claines, Worcester, Worcestershire WR3 7RY (GB).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SECURITY DEVICE FOR A DOOR



(57) Abstract: A security device for limiting opening of an inwardly-openable door (4) in a building. The device comprises keep means (6) adapted to be secured to a region of an inside surface (8) of the door (4) and arm means (12) adapted to be swivelably secured at a first end (14) thereof to an interior surface (16) of the building fixed relative to the door (4). The arm means (12) is adapted to be manually swivelled between a first position, clear of the door (4), and a second position in which a second end (18) of the arm means (12) abuttingly engages the keep means (6) to limit opening of the door (4). At least one spring means is provided incorporated in the keep means (6) and/or the arm means (12) to absorb energy upon engagement of the second end (18) of the arm means (12) with the keep means (6).

WO 03/091520 A1

- 1 -

SECURITY DEVICE FOR A DOOR

This invention relates to a security device for a building and which is operable to limit opening of an inwardly-openable door in the building, particularly to prevent forced entry by an intruder while allowing sufficient opening of the door to enable identity of a person outside the door to be determined.

10 The present invention also provides for an alarm to be actuated when forced entry is attempted through the door.

According to the present invention there is provided a security device for limiting opening of an inwardly-openable door in a building, the device comprising keep means adapted to be secured to a region of an inside surface of the door, and arm means adapted to be swivelably secured at a first end thereof to an interior surface of the building fixed relative to the door, the arm means being adapted to be manually swivelled between a first position, clear of the door, and a second position in which a second end of the arm means abuttingly engages the keep means to limit opening of the door, at least one spring means being provided incorporated in the keep means and/or the arm means to absorb energy upon engagement of the second end of the arm means with the keep means.

The spring means may additionally serve to recoil and effect or assist closure of the door in event of the door being undesirably jolted inwardly from outside.

The region of the inside surface of the door to which the keep means is adapted to be secured may be adapted to be adjacent to a hinged edge of the door.

- 2 -

The interior surface of the building to which the arm means is adapted to be swivelably secured may be a wall of the building adjacent to a hinged edge of the door, and such as extending at substantially ninety degrees to the door when the door is closed. Intermediate support means, such as of block form, may be provided for securing to the wall and adapted to have the arm means swivelably secured thereto.

10 The keep means may comprise an elongate block adapted to be secured to the region of the inside surface of the door and having at a first end region thereof an outwardly open slot, such as of U-shape, for receiving the second end of the arm means.

15 The elongate block may be adapted to be secured to the region of the inside surface of the door by way of a first base plate to which it is secured, and which may be apertured to receive one or more securing means, such as one or more threaded fasteners.

The elongate block may incorporate an axial cylinder having an end open to the slot and in which is received a piston means and a first compression spring serving as the at least one spring means, the piston means being adapted to be contacted, and displaced to a limited extent in the cylinder against the first compression spring, by the second end of the arm means when forceful pressure is applied to the door to attempt opening of the door.

The piston means may have a first face provided with a recess for receiving the second end of the arm means and may have a second face, opposite the first face, provided

- 3 -

with a protrusion for accommodating the first compression spring.

The outwardly open slot at the first end region of the elongate block may have an end portion sloping inwardly towards the piston means in the cylinder to direct the second end of the arm means into alignment with the piston means and the cylinder.

10 The axial cylinder may extend through the elongate block to a second end region of the elongate block opposite to the first end region of the block and may be closed by a cap means, which may be threaded into or onto the second end region of the elongate block.

15

The arm means, at least at the second end thereof, may be of substantially solid cylindrical form.

The first end of the arm means may be provided with a bearing component, secured thereto or integral therewith, which is rotatable in a mounting component adapted to be secured to the interior surface of the building fixed relative to the door. The bearing component may be arranged for rotation in the mounting component about a substantially vertical axis, when the mounting component is secured to the interior surface of the building, and such that the arm means is able to be swivelled between the first and second positions in a substantially horizontal plane.

30

The mounting component may comprise upper and lower portions journaled to rotatably receive the bearing component therebetween and secured to a second base plate which may be apertured to receive one or more securing means, such as one or more threaded fasteners.

35

- 4 -

A second compression spring may be incorporated with the arm means such that the first end of the arm means is slidably secured to the bearing component against the second compression spring and with the arm means
5 displaceable in its axial direction relative to the bearing component.

The second compression spring may reinforce or replace the function of the first compression spring.

10

Switch means may be incorporated in the bearing component and adapted to be actuated by axial displacement of the arm means relative to the bearing component against the second compression spring to operate an alarm means, such
15 as an audible alarm means, to provide a warning that forced entry through the door is being attempted. Such alarm means may be incorporated in a cavity in the mounting component, or may be at a remote location.

20 One or more batteries may be incorporated in a cavity provided in the mounting component, such cavity being suitably closed by a cap means which may threadedly engage the mounting component.

25 The second compression spring may have a spring rate which is lower than that of the first compression spring, whereby the switch means is actuated before the first compression spring is fully compressed.

30 The device may substantially comprise metal, such as brass or aluminium. When the metal is aluminium, it may be surface-anodised.

For a better understanding of the present invention and
35 to show more clearly how it may be carried into effect,

- 5 -

reference will now be made, by way of example, to the accompanying drawings in which:

Figure 1 is a perspective view of an embodiment of a security device according to the present invention installed in association with a door in a building;

Figure 2 is a plan view of the security device of Figure 1;

10

Figure 3 is an exploded view of keep means forming part of the security device of Figures 1 and 2;

Figure 4 is a perspective view of an elongate block in the keep means of Figure 3;

15

Figure 5 is a perspective view of the elongate block of Figure 4, showing a piston means provided in a cylinder thereof;

20

Figure 6 is a perspective view of the elongate block of Figure 5 secured to a base plate;

Figure 7 is an exploded view of swivelably-mounted arm means forming part of the security device of Figures 1 and 2;

25

Figure 8 is a perspective view of part of the arm means of Figure 7 mounted in a bearing component; and

30

Figure 9 is a perspective view of the assembled swivelably-mounted arm means of Figure 7, provided with an alarm means.

- 6 -

Referring to Figures 1 and 2, a security device 2 is provided for limiting opening of an inwardly-openable door 4 in a building. The device 2 has a keep means 6 adapted to be secured to a region of an inside surface 8 of the door 4, adjacent to a hinged edge 10 of the door 4.

The device 2 also has an arm means 12 which is adapted to be swivelably secured at a first end 14 thereof to an interior surface 16 of the building fixed relative to the door 4. The interior surface 16 of the building suitably comprises an internal wall of the building adjacent to the hinged edge 10 of the door 4 and suitably extending at substantially ninety degrees to the door 4 when the door is closed.

If required, where a suitable wall extending at ninety degrees is not available, an intermediate support means (not shown), such as of block form, may be provided for securing to the wall comprising the surface 16 and adapted to have the arm means 12 swivelably secured thereto.

The arm means 12 is arranged to be manually swivelled between a first position, as shown by the dotted outline in Figure 1, in which it is clear of the door, and a second position in which a second end 18 thereof abuttingly engages the keep means 6 to limit opening of the door 4. In the first position of the arm means 12, the door 4 is openable inwards in a normal unrestricted manner.

The arm means 12 is suitably of substantially solid cylindrical form, at least at the second end 18 thereof.

- 7 -

As will be described in detail hereinafter, at least one spring means is incorporated in the keep means 6 and/or the arm means 12 and operating in an axial direction of the arm means 12. Such spring means is or are arranged to absorb energy upon dynamic engagement of the second end 18 of the arm means 12 with the keep means 6 and reduces the likelihood of damage to the door 4 and its frame and hinges.

10 The spring means additionally serves or serve to recoil and effect or assist closure of the door 4 by effecting rebound of the door 4 in event of the door being undesirably jolted by an intruder attempting forcible entry from outside.

15

As will also be described in detail hereinafter, the security device 2 may be adapted to operate an alarm means when forcible entry through the door 4 is attempted.

20

The security device 2 of the present invention accordingly is readily arranged to allow complete freedom of opening of the door 4, when the arm means 12 is in the first position shown by the dotted outline in Figure 1, or allow only a predetermined limited extent of opening of the door 4 when the arm means 12 is abuttingly engaged with the keep means 6. Such predetermined limited extent of opening may be sufficient to provide a gap to allow identification of a person outside the door 4 and/or to permit receipt of items, such as mail, through the gap.

30

The security device 2 substantially comprises metal, such as brass or aluminium. When the metal is aluminium, its surface may be anodised.

35

- 8 -

Referring additionally now to Figures 3 to 6, the keep means 6 comprises an elongate block 20 secured to a first base plate 22 by means of threaded fasteners 24 passing through holes 26 in the first base plate 22 and into threaded holes 28 provided in the elongate block 20. The first base plate 22 is provided with holes 30 therein through which screws 32 are passed for securing the keep means 6 to the inside surface of the door 4.

- 10 The elongate block 20 is provided, at a first end region 34 thereof, with an outwardly open U-shaped slot 36 for receiving the second end 18 of the arm means 12.

The elongate block 20 incorporates an axial cylinder 38 (Figure 4) having an end open to the U-shaped slot 36 and in which is received a piston 40 and a first compression spring 42. The piston 40 has a first face 44 provided with a recess for abuttingly receiving the second end 18 of the arm means 12 when the latter is located in the U-shaped slot 36.

The piston 40 also has a second face provided with a protrusion 46 which fits inside one end of the first compression spring 42.

25

The axial cylinder 38 extends through the elongate block 20 to a second end region 48 of the elongate block 20 and is closed by a cap means 50 which is threaded into, but could be threaded onto, the second end region 48 of the elongate block 20. The cap means 50 is provided with a protrusion 52 for locating in the first compression spring 42.

When the arm means 12 is engaged with the U-shaped slot 36, and forceful pressure is applied to the door 4 to

- 9 -

attempt to open the door, the second end 18 of the arm means abuttingly engages the recessed first face 44 of the piston 40 and displaces the piston 40 to a limited extent against the first compression spring 42, thus
5 absorbing energy resulting from forcible movement of the door 4 and preventing damage to the door and its ancillaries, such as its frame and hinges.

The first compression spring 42 also recoils and has the
10 effect of slamming shut the door 4 as an additional safety feature.

In order to assist alignment of the second end 18 of the arm means 12 with the piston 40, the outwardly open slot
15 36 at the first end region 34 of the elongate block 20 may have an end portion 54 sloping inwardly towards the piston 40 to direct the second end 18 of the arm means 12 towards the piston 40.

20 Referring now to Figures 7 to 9, in addition to Figure 2, the first end 14 of the arm means 12 is provided with a bearing component 56 which is rotatable in a mounting component comprising upper and lower portions 58 and 60. The mounting component 58, 60 is secured to a second base
25 plate 62 by means of threaded fasteners 64 passing through holes 66 in the second base plate 62. The upper and lower portions 58, 60 comprising the mounting component are suitably journaled to rotatably receive the bearing component 56 therebetween, sealing rings 68,
30 such as of rubber or neoprene being provided at the interfaces between the bearing component 56 and the mounting component 58, 60.

The second base plate 62 is provided with holes 70 by
35 means of which the second base plate 62 is secured by

- 10 -

screws 72 directly or indirectly to the interior surface 16, such as an inner wall, of the building.

The second base plate 62 with its assembled components is
5 secured to the interior surface 16 of the building such
that the bearing component 56 is rotatable in the
mounting component 58, 60 about a substantially vertical
axis and such that the arm means 12 is able to be
swivelled between its first and second positions in a
10 substantially horizontal plane.

A recess 74 is provided in the second base plate 62 to
facilitate rotation of the bearing component 56.

15 A second compression spring 76 is arranged on a stepped
portion 78 at the first end 14 of the arm means 12 and
operating such that the first end 14 of the arm means 12
is slidably secured in a sleeve portion 80 of the bearing
component 56 against the second compression spring 76.
20 With this arrangement, the arm means 12 is displaceable
in its axial direction relative to the bearing component
56. A clip 82 engages a hole 84 in the stepped portion
78 at the first end 14 of the arm means 12 to retain the
first end 14 of the arm means 12 in the bearing component
25 56.

A switch means 86 (Figure 9) can be incorporated in the
bearing component 56 and adapted to be actuated by axial
displacement of the arm means 12 relative to the bearing
30 component 56 against the second compression spring 76, to
operate an alarm means 88, such as a siren or other
audible alarm means, to provide a warning that forced
entry through the door 4 is being attempted. Such an
alarm means 88 can be incorporated in a cavity in the
35 mounting component 58, 60, such as in the lower portion

- 11 -

60 of the mounting component. However, the alarm means 88 could be arranged at a remote location and/or could form part of a general security alarm system provided in the building.

5

One or more batteries 90 for powering the alarm means 88 can be provided inside the mounting component 58, 60, such as in a cavity in the upper portion 58 of the mounting component. Access to the battery or batteries 10 90 is suitably arranged by means of a cap 92 threadedly engaging the mounting component 58, 60.

The second compression spring 76 suitably has a spring rate which is lower than that of the first compression 15 spring 42, whereby the switch 86 is actuated before the first compression spring 42 is fully compressed.

The second compression spring 76 may also reinforce or replace the function of the first compression spring 42.

CLAIMS

1. A security device (2) for limiting opening of an inwardly-openable door (4) in a building, characterised
5 in that the device comprises keep means (6) adapted to be secured to a region of an inside surface (8) of the door (4), and arm means (12) adapted to be swivelably secured at a first end (14) thereof to an interior surface (16) of the building fixed relative to the door (4), the arm
10 means (12) being adapted to be manually swivelled between a first position, clear of the door (4), and a second position in which a second end (18) of the arm means (12) abuttingly engages the keep means (6) to limit opening of the door (4), at least one spring means being provided
15 incorporated in the keep means (6) and/or the arm means (12) to absorb energy upon engagement of the second end (18) of the arm means (12) with the keep means (6).

2. A device as claimed in claim 1, characterised in
20 that the spring means additionally serves to recoil and effect or assist closure of the door (4) in event of the door (4) being undesirably jolted inwardly from outside.

3. A device as claimed in claim 1 or 2, characterised
25 in that the region of the inside surface (8) of the door (4) to which the keep means (6) is adapted to be secured is adapted to be adjacent to a hinged edge (10) of the door (4).

30 4. A device as claimed in any preceding claim, characterised in that the interior surface (16) of the building to which the arm means (12) is adapted to be swivelably secured is a wall of the building adjacent to a hinged edge (10) of the door (4), and such as extending

- 13 -

at substantially ninety degrees to the door (4) when the door (4) is closed.

5. A device as claimed in any preceding claim,
5 characterised in that intermediate support means is provided for securing to the wall and adapted to have the arm means (12) swivelably secured thereto.

6. A device as claimed in claim 5, characterised in
10 that the intermediate support means is of block form.

7. A device as claimed in any preceding claim,
characterised in that the keep means (6) comprises an elongate block (20) adapted to be secured to the region
15 of the inside surface (8) of the door (4) and having at a first end region (34) thereof an outwardly open slot (36) for receiving the second end (18) of the arm means (12).

8. A device as claimed in claim 7, characterised in
20 that the outwardly open slot (36) is of U-shape.

9. A device as claimed in claim 7 or 8, characterised in that the elongate block (20) is adapted to be secured to the region of the inside surface (8) of the door (4)
25 by way of a first base plate (12) to which it is secured.

10. A device as claimed in claim 9, characterised in that the first base plate (12) is apertured to receive at least one securing means (24).

30

11. A device as claimed in claim 10, characterised in that the at least one securing means is a threaded fastener (24).

- 14 -

12. A device as claimed in any of claims 7 to 11, characterised in that the elongate block (20) incorporates an axial cylinder (38) having an end open to the slot and in which is received a piston means (40) and
5 a first compression spring serving as the at least one spring means, the piston means (40) being adapted to be contacted, and displaced to a limited extent in the cylinder against the first compression spring (42), by the second end (18) of the arm means (12) when forceful
10 pressure is applied to the door (4) to attempt opening of the door (4).

13. A device as claimed in claim 12, characterised in that the piston means (40) has a first face (44) provided
15 with a recess for receiving the second end (18) of the arm means (12).

14. A device as claimed in claim 13, characterised in that the piston means (40) has a second face, opposite
20 the first face (44), provided with a protrusion for accommodating the first compression spring (42).

15. A device as claimed in claims 12, 13 or 14, characterised in that the outwardly open slot at the
25 first end region of the elongate block (20) has an end portion (54) sloping inwardly towards the piston means (40) in the cylinder to direct the second end (18) of the arm means (12) into alignment with the piston means (40) and the cylinder.

30

16. A device as claimed in any one of claims 12 to 15, characterised in that the axial cylinder (38) extends through the elongate block (20) to a second end region (48) of the elongate block (20) opposite to the first end
35 region of the block.

- 15 -

17. A device as claimed in any one of claims 12 to 16, characterised in that the axial cylinder (38) is closed by a cap means (50).

5 18. A device as claimed in claim 17, characterised in that the cap means (50) is threaded into the second end region of the elongate block (20).

10 19. A device as claimed in claim 17, characterised in that the cap means is threaded onto the second end region of the elongate block (20).

15 20. A device as claimed in any preceding claim, characterised in that the arm means (12), at least at the second end (18) thereof, is of substantially solid cylindrical form.

20 21. A device as claimed in any preceding claim, characterised in that the first end (14) of the arm means (12) is provided with a bearing component (56), secured thereto or integral therewith, which is rotatable in a mounting component adapted to be secured to the interior surface (16) of the building fixed relative to the door (4).

25 22. A device as claimed in claim 21, characterised in that the bearing component (56) is arranged for rotation in the mounting component about a substantially vertical axis, when the mounting component is secured to the interior surface (16) of the building, and such that the arm means (12) is able to be swivelled between the first and second positions in a substantially horizontal plane.

35 23. A device as claimed in claim 21 or 22, characterised in that the mounting component comprises upper (58) and

- 16 -

lower (60) portions journaled to rotatably receive the bearing component (56) therebetween and secured to a second base plate (62) which is apertured to receive one or more securing means (64).

5

24. A device as claimed in claim 23, characterised in that the securing means comprises threaded fasteners (64).

10 25. A device as claimed in any one of claims 21 to 24, characterised in that a second compression spring (76) is incorporated with the arm means (12) such that the first end (14) of the arm means (12) is slidably secured to the bearing component (56) against the second compression
15 spring (76) and with the arm means (12) displaceable in its axial direction relative to the bearing component (56).

26. A device as claimed in claim 25, characterised in
20 that the second compression spring (76) reinforces the function of the first compression spring (42).

27. A device as claimed in claim 25, characterised in that the second compression spring (76) replaces the
25 function of the first compression spring (42).

28. A device as claimed in any one of claims 25 to 27, characterised in that switch means (86) is incorporated in the bearing component (56) and adapted to be actuated
30 by axial displacement of the arm means (12) relative to the bearing component (56) against the second compression spring (76) to operate an alarm means (88) to provide a warning that forced entry through the door (4) is being attempted.

35

- 17 -

29. A device as claimed in claim 28, characterised in that the alarm means (88) is an audible alarm means.

30. A device as claimed in claim 28 or 29, characterised in that the alarm means is incorporated in a cavity in the mounting component.

31. A device as claimed in claim 28 or 29, characterised in that the alarm means is at a remote location.

10

32. A device as claimed in any one of claims 21 to 31, characterised in that one or more batteries (90) are incorporated in a cavity provided in the mounting component.

15

33. A device as claimed in claim 32, characterised in that the cavity is suitably closed by a cap means which threadedly engages the mounting component.

20 34. A device as claimed in any one of claims 28 to 33, characterised in that the second compression spring (76) has a spring rate which is lower than that of the first compression spring (42), whereby the switch means (86) is actuated before the first compression spring (42) is fully compressed.

25

35. A device as claimed in any preceding claim, characterised in that the device substantially comprises metal.

30

36. A device as claimed in claim 35, characterised in that the metal is selected from brass and aluminium.

37. A device as claimed in claim 36, characterised in that the aluminium is surface-anodised.

35

1 / 8

FIG 1









FIG 2




3 / 8

FIG 3










FIG 8




FIG 9

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 03/01626

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 E05C19/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 E05C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EP0-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|---|--------------------------|
| X A | US 5 039 147 A (MOON ALAN ET AL) 13 August 1991 (1991-08-13) column 2, line 40 - line 62 column 3, line 7 - line 26; figure --- | 1-11, 20-24 25, 28 |
| A | US 4 070 049 A (BREWER JACK J) 24 January 1978 (1978-01-24) column 4, line 51 - column 5, line 24; figure --- | 1 |
| A | US 6 058 563 A (BUCKNELL MARTIN JOHN) 9 May 2000 (2000-05-09) the whole document --- | 1 |
| A | GB 2 186 909 A (FROST FRANK HARRY) 26 August 1987 (1987-08-26) the whole document ----- | 1 |

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

12 August 2003

Date of mailing of the international search report

21/08/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl
Fax: (+31-70) 340-3016

Authorized officer

Pieracci, A

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 03/01626

| Patent document cited in search report | | Publication date | Patent family member(s) | Publication date |
|---|---|---------------------|----------------------------|---------------------|
| US 5039147 | A | 13-08-1991 | EP 0336947 A1 | 18-10-1989 |
| | | | WO 8903469 A1 | 20-04-1989 |
| | | | GB 2219343 A , B | 06-12-1989 |
| US 4070049 | A | 24-01-1978 | NONE | |
| US 6058563 | A | 09-05-2000 | NONE | |
| GB 2186909 | A | 26-08-1987 | NONE | |